

Colour



This product has exquisite appearance, small size, multi-function housing, ingenious anti-theft design and high integration, can be widely used in residential garage and other AC slow charging scene.

Datasheet	Parameter	IEC
		ZL-IEC-AC16-S&P-3
Appearance and structure	Product size	253*180*59.5mm
	Weight	6kg
	Cable length	5m
	Shell&house material	PC by UL certificates
	Cable material	TPU
	Terminal material	Copper
	Charging interface type	EN 62196-1:2014;EN 62196-2:2017
	Gun color	Black/white/mix color options
	Start mode	With RFID card/ No RFID card
	Certification	CE/RoHS/Reach
	Production time-1000pcs	20-25 days
	Current/KW	11KW, 16A 3phase
Electrical performance	Input & output	400V AC
	input frequency	50HZ/60Hz
	Relay	40A
	Waterproof grade	IP66
Safety	Low temperature resistance	-45°C
	High temperature resistance	65°C
	Over Voltage protection	✓
	Over Current protection	✓
	Short circuit protection	✓
	Ground Protection	✓
	Over Temperature Protection	✓
	Short Voltage protection	✓
	Lighting Protection	✓
	Residual Current protection	✓
	surge Protection	✓
	Under Voltage protection	✓
	Under Current protection	✓
	Under Temperature Protection	✓
	LED indicator light	✓
	WIFI	NO
	LCD	NO
	Current adjusting	NO
	Relative humidity	5%~95%
	Maximum altitude	<2000M
	cooling	natural air cooling
	standby power consumption	<8W